


7MM VINYL AQUATILE

Features

- Designed for residential & light commercial use
- Realistic texture & finish
- Low maintenance
- High-density core for superior stability
- Easy click installation



waterproof



drop-lock flooring



light commercial warranty*



residential warranty



AC5 Rating




CERTIFIED BY SCS Global Services




scratch resistant

* Light Commercial Use covers areas with moderate foot traffic and occasional rolling loads, excluding heavy equipment, industrial traffic, or continuous high-impact wear.


Accessories



Stair Nosing[†]
2400 × 55 × 18 mm



Reducer
2400 × 45 × 12 mm



T-Moulding
2400 × 45 × 12 mm

For illustrative purposes only, each product contains its own distinct character & color variation. Product dimensions are nominal and provided as a guideline.

Note: Vinyl flooring can be installed in a single room / area up to 36 linear feet in length or 30 linear feet width. Installations in rooms / areas over 36 linear feet in length or 30 linear feet width must use T- moldings. Otherwise, the warranty will be void.

[†] Stair nosing is available in either flush or overlap profiles. The specific type of stair nosing offered may vary depending on the chosen flooring color.

Product Information

Structure

Rigid Core Vinyl with HUSSSH! pad

Gloss Level

5°~8°

Dimension (H × L × W)

7mm × 305mm × 610mm
12" × 24"

Weight

40 lbs. per box, 2400 lbs. per skid

Underlayment

1.5 mm IXPE (HUSSSH)

Edge Detail

V-groove

Packaging

16.03 sqft per box, 8pcs per box, 60 Boxes per skid

Wear Layer

0.5 mm | 20 mil

Finish

Ceramic UV

Warranty

30 years residential
5 years light commercial

Technical Information

Sound Reduction

IIC=51dB, ΔIIC=23dB

Sound Transmission

Rw+C=49dB Rw+Ctr=46dB

Lock System

Drop Lock

Click Type

Valinge 5G with plastic lock

Installation

Float, No Nails

Suitable Location

ON, Above or Below Grade

Temperature Range

55 – 95 °F | 12 – 35 °C

Radiant Heat Suitable

Suitable For Use with Hydronic Systems Only, up to 26 °C

Rating

AC5

Certification

FloorScore

Disclaimer

Please refer to the full official installation guidelines for complete details.

- 1. Official Guidelines Must Be Followed:** Installation, subfloor preparation, and site conditions must strictly align with our official installation guidelines. We are not responsible for damages caused by improper installation.
- 2. Climate-Controlled Indoor Use Only:** This product is designed exclusively for interior, climate-controlled environments.
- 3. The warranty shall be void under conditions including, but not limited to, the following:**
 - Use of any additional underlayment.
 - Installation beneath cabinets, kitchen islands, or other heavy fixtures.

Note: Wheeled or office chairs are highly discouraged; any resulting wear or damage is not covered.